

## Super Leichtlauf 10W-40

### Description

Low-friction motor oil based on synthetic technology. For the high requirements of modern, high-performance gasoline and diesel engines without maintenance interval extension. Saves fuel, provides optimum protection against wear and has a beneficial effect on sealing materials and thus on the leaktightness of engines. Therefore highly suitable for year-round use in vehicles with mileages of over 100,000 km.

### Properties

- instant lubrication after cold start
- outstanding engine cleanliness
- miscible with all commercially available motor oils
- regenerates seals
- high shear stability
- especially suitable for vehicles with mileages over 100,000 km
- high lubrication reliability
- saves fuel and reduces pollutant emissions
- maintains seals
- smooth engine running
- excellent wear protection
- optimum stability to aging
- tested for turbochargers and catalytic converters

### Approvals

ACEA A3 • ACEA B4 • API SN • MB-Approval 229.3 • VW 501 01 • VW 505 00

**LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required**

Fiat 9.55535-D2 • Fiat 9.55535-G2 • MB 229.1 • Peugeot Citroen (PSA) B71 2300 • Renault RN 0700 • Renault RN 0710

### Technical data

SAE class (engine oils)	10W-40 SAE J300
Density at 15 °C	0,87 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	95,5 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	14 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -30 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -25 °C (CCS)	≤ 7000 mPas ASTM D5293



### Technical data

Viscosity index	150 DIN ISO 2909
HTHS at 150°C	≥ 3,5 mPas ASTM D5481
Pour point	-36 °C DIN ISO 3016
Evaporation loss (Noack)	12 % CEC-L-40-A-93
Flash point	232 °C DIN ISO 2592
Total base number	10,8 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color number (ASTM)	2,5 DIN ISO 2049

### Areas of application

Ideal for vehicles with mileages of over 100,000 km and for modern gasoline, diesel and turbocharged engines.

### Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed. Optimum effect only when the product is used unmixed.

### Available pack sizes

1 l Canister plastic	9503 BOOKLET
1 l Canister plastic	21236 ALGERIEN-GB-ARAB-F
1 l Canister plastic	21106 D-GB-CN
4 l Canister plastic	9504 BOOKLET
4 l Canister plastic	20670 ALGERIEN-GB-ARAB-F
4 l Canister plastic	20698 D-GB-CN

# Super Leichtlauf 10W-40

### Available pack sizes

5 l Canister plastic	9505 BOOKLET
5 l Canister plastic	20671 ALGERIEN-GB-ARAB-F
20 l Canister plastic	1304 D-GB-I-E-P
60 l Drum sheet metal	1302 D-GB
205 l Drum sheet metal	1303 D-GB

**Our information is based on thorough research and may be considered reliable, although not legally binding.**