

Description

Fully synthetic Electronic Spray that is compatible with plastics for the cleaning and care of contaminated electrical parts. Protects the electronic parts against corrosion by driving out moisture and water. Infiltrates the oxide and sulfide layers, thereby reducing contact resistance, protecting the electronic parts and ensuring operational reliability. No adverse effects on plastic and rubber components. The quickdrying formula does not leave residues and is siliconefree.

Properties

- reduces contact resistance
- leaves no residues
- neutral behavior on rubber and plastics
- silicone-free
- also suitable for overhead work
- good corrosion protection
- penetrates and drives out moisture
- cleans contaminated contacts

Technical data

Color / appearance	blue
Base	synthetic oil
Viscosity at 40 °C	49,5 mm²/s
Viscosity at 100 °C	7 mm²/s
Viscosity index	145
Pour point	-53 °C DIN ISO 3016
Evaporation loss (Noack)	2,1 Gew% DIN ISO 2909
Water content	40 ppm Ω · cm DIN 51 581
Neutralization number	0,03 mg KOH/g DIN 51 777 T 1
Copper corrosion	0-1 DIN 51 809
Specific electrical volume resistance at 20 °C	1,6 · 10º Ω · cm
Odor	characteristic
Form	liquid

Areas of application

Used for the maintenance, care, cleaning and protection of all electrical components on the vehicle such as plug and terminal connections, lamp sockets, cable distribution boxes, switch elements, relays, ignition distributors, contact breakers, starters, alternators, fuses, battery terminals and antennae and



for the lubrication of fine mechanical parts.

Application

Spray electric components before assembly, then assemble. With severely corroded contacts, allow to act for longer. Rub off loosened corrosion residues with a cloth or brush. The fold-out capillary tube ensures precision spraying. With the capillary tube folded in, large areas are sprayed. Also sprays when inverted. **Note:** After spraying on, allow a flash-off period of 10 min. before connecting the component to a power supply.

Available pack sizes

400 ml Can aerosol	7386 D-GB-I-E-P
400 ml Can aerosol	9913 GB-DK-FIN-N-S

Our information is based on thorough research and may be considered reliable, although not legally binding.