

Product information

megol Getriebeöl ATF Variable Low Viscosity



Description

The next generation of automatic transmission fluid based on HC synthetic base oils in combination with state-of-the-art, powerful additives. Its low viscosity helps to achieve a more efficient fuel consumption and enables optimum shifting under all operating conditions. It meets the requirements of a large number of global automatic transmission and vehicle manufacturers. Follow the manufacturer's instructions.



Meguin also recommends this product for vehicles that are subject to the following specifications

Aisin Warner AW-1 • BMW M-1375.4 • Dexron VI • Fiat 9.55550-AV5 • Ford Mercon LV • JWS 3324 (Aisin Warner) • Honda ATF 3.1 • Hyundai SP-IV • Mazda ATF FZ • MB 236.12 • MB 236.14 • Nissan AT-Matic S Fluid • Toyota WS • VW G 055 005 • VW G 055 540 • VW G 060 162

Available pack sizes

1.000 l Container	33035
	D-GB

Characteristic data

Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	28,5 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	5,8 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	≤ 15000 mPas ASTM D 2983-09
Viscosity index	155 DIN ISO 2909
Pour point	-48 °C DIN ISO 3016
Flash point	210 °C DIN ISO 2592
Color / appearance	bräunlich/brownish
Color number (ASTM)	4 DIN ISO 2049

Application

Shake well before use.

Available pack sizes

1 l Can plastic	33007 D-GB-F-RUS-GR-ARAB
20 l Canister plastic	33010 D-GB
200 l Black plate barrel	33084 D-GB