

Product information

megol Getriebeoel CVT Dynamik



Description

High-performance automatic transmission fluid specially formulated for use in the latest CVT generation. The basis of selected base oils and special additives offers the best possible anti-foam protection, which is necessary for CVTs. It also features a good stability against aging and oxidation. megol CVT Dynamic is tried and tested, most notably in the Autotronic transmissions used in the Mercedes A-Class and B-Class, but it can also be used in many continuously variable automatic transmissions developed by other manufacturers (e.g. Audi Multitronic).



Available pack sizes

20 l Canister plastic 3172
DE-EN

Note the manufacturer's instructions!

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Ford CVT23 • Ford CVT30 • Ford Mercon C • Honda HMMF • Jeep NS-2 • Jeep CVTF+4 • MB 236.20 • Mini Cooper (E2L 799) • Mitsubishi CVTF-J1 • Mitsubishi CVTF-J4 • Nissan CVT NS-2 Fluid • Subaru NS-2 • Suzuki CVT Green1 • Suzuki NS-2 • Suzuki TC • Toyota TC • Subaru Lineartronic CVTF • VW G 052 180 • VW G 052 516 • Dodge NS-2 • Dodge CVTF+4 • GM/Saturn DEX-CVT

Characteristic data

Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	33,5 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	7,2 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	<= 20000 mPas ASTM D 2983-09
Viscosity index	185 DIN ISO 2909
Flash point	200 °C DIN ISO 2592
Pour point	-45 °C DIN ISO 3016
Color number (ASTM)	L 2,0 DIN ISO 2049

Application

Shake well before use.

Available pack sizes

1 l Can plastic 9452
AR-DE-EL-EN-FR-RU