### **Product information**

## Special Tec AA 0W-16

# PI 15/12/02/2021 LIQUI

### **Description**

Premium class low-friction motor oil. Provides outstanding protection against wear, lowers oil and fuel consumption, keeps the engine clean and ensures fast oil penetration.

### **Properties**

- optimum oil pressure under all operating conditions
- high shear stability
- instant lubrication after cold start
- long engine service life
- smooth engine running
- excellent wear resistance
- outstanding engine cleanliness
- optimum stability to aging
- excellent high and low temperature behavior
- high lubrication reliability
- tested for turbochargers and catalytic converters
- saves fuel and reduces pollutant emissions

### **Approvals**

API SP • ILSAC GF-6B

# LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

Honda • Lexus • Suzuki • Toyota

### **Technical data**

SAE class (engine oils)	0W-16 SAE J 300
Density at 15 °C	0,845 g/cm³ DIN 51757
Viscosity at 40 °C	38 mm²/s

ASTM D 7042-04

Viscosity at 100 °C 7,2 mm<sup>2</sup>/s

ASTM D 7042-04

Viscosity at -40 °C (MRV) < 60000 mPas

ASTM D 4684

Viscosity at -35 °C (CCS)  $\leq$  6200 mPas

**ASTM D 5293** 

Viscosity index 155

**DIN ISO 2909** 

HTHS at 150°C  $\Rightarrow$  2,3 mPas

**ASTM D 5481** 

Pour point -45 °C

DIN ISO 3016

Evaporation loss (Noack) 12,5 %

CEC-L-40-A-93

Flash point 224 °C

**DIN ISO 2592** 



#### Technical data

Total base number	8,3 mg K0H/g
	DIN ISO 3771
Sulfate ash	0,9 g/100g

Sulfate ash 0,9 g/100g DIN 51575

Color number (ASTM) L 2,5

**DIN ISO 2049** 

### Areas of application

Ideal for modern Asian and American gasoline engines. Especially where there are long intervals between oil changes and high requirements on the engine.

### **Application**

The specifications and instructions from the assembly or vehicle manufacturer must be followed. Optimum effectiveness is only possible when the product is used unmixed.

### Available pack sizes

1 l Canister plastic	21326 BOOKLET
4 l Canister plastic	21327 BOOKLET
5 l Canister plastic	21328 BOOKLET
20 l Canister plastic	21324 D-GB-I-F-E-P-DK-FIN-N-S
60 l Drum sheet metal	21325 D-GB
205 l Drum sheet metal	21589 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.