

# Product information

## Hydraulic Lifter Additive

PI 40/12/02/2021



### Description

High-performance additive that damps down noise generation of contaminated and sticky hydraulic tappets. Cleans oil holes and ducts in the oil circuit and ensures that they once again work optimally. Improves the function of timing chain tensioners filled with oil pressure, which can result in the reduction of timing chain noise.

### Properties

- dampens hydraulic tappet noise
- cleans valve bores
- improves the lubrication properties of the oil
- tested for turbochargers and catalytic converters

### Technical data

Color / appearance	amber
Appearance / properties	viscous liquid
Density at 20 °C	0,887 g/cm <sup>3</sup> DIN 51757
Form	liquid
Odor	characteristic
Viscosity at 20 °C	1100 mPas

### Areas of application

For all gasoline and diesel engines. Can be mixed with all commercially available motor oils.

### Comment

**Not suitable for motorcycles with a wet clutch!**

### Application

Contents (300 ml) sufficient to treat up to 6 liters of motor oil. The product can be added at any time. After adding, run the engine until warm. To guarantee a lasting effect, use the additive after each oil change.

### Available pack sizes

300 ml Can sheet metal	2770 GB-GR-I
300 ml Can sheet metal	8345 D-PL-BG
300 ml Can sheet metal	8354 D-E-P
300 ml Can sheet metal	8367 GB-ARAB-F
300 ml Can sheet metal	8382 D-H-RO
300 ml Can sheet metal	8338 DK-N-S-FIN

### Available pack sizes

300 ml Can sheet metal	2783 GB-AUS
300 ml Can sheet metal	20801 D-GB-SLO-SRB-HR
300 ml Can sheet metal	1009 D-F-NL

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

