Product information

Oil Additive

PI 39/12/02/2021



Description

Colloidal solid lubricant suspension based on molybdenum disulfide (MoS2) in mineral oil. The product forms a high-load lubricating film on all rubbing and sliding surfaces. This in turn reduces friction, providing for smoother operation of assemblies and greater engine economy. Tested for turbochargers and catalytic converters.



Properties

•	
- reduces oil and fuel consumption	
- reduces running-in and operating we	ar
and demonstra	

- no deposits

- highest thermal stability

- absolutely compatible with filters

- miscible with all commercially available motor oils

- increases smooth operation

- outstanding emergency-running properties

Technical data

Density at 20 °C

Base	MoS2 -Suspension
Color / appearance	black
Solids content	~ 3 %

0,9 g/cm³ DIN 51757

Flash point 201 °C

DIN ISO 2592

Pour point -20 °C

DIN ISO 3016

Odor characteristic

Form liquid Viscosity at 40 °C 95 mm²/s

Areas of application

Added to the lubricating oils of engines, compressors, pumps and especially motor vehicle engines (gasoline and diesel). Mixable with all commercially available motor oils.

Comment

The maximum dosage for motorcycles with a wet clutch is 2 %!

Application

Add 5 % (50 ml per liter of oil) of Oil Additive to motor oil; in motorbikes with a wet clutch add 2 % (20 ml per liter of oil). Can be added to motor oil at any time. Shake container before use.

Available pack sizes

125 ml Can sheet metal 1800 GB-GR-I Available pack sizes

125 ml Can sheet metal 8352 D-F-P

125 ml Can sheet metal 8378

D-H-R0 125 ml Can sheet metal 8341

D-PL-BG

125 ml Can sheet metal 21500

F-D

125 ml Can sheet metal 1011

D-F-NL

150 ml Can sheet metal 20628

D-E-P

200 ml Can sheet metal 7178

GB-GR-I

200 ml Can sheet metal 20685

D-GB-CN

200 ml Can sheet metal 1012

D-F-NI

300 ml Can sheet metal 2500

D-E-P

300 ml Can sheet metal 2805

DK-N-S-FIN

300 ml Can sheet metal 2591

GB-GR-I

300 ml Can sheet metal 2182

2182 D-H-R0

300 ml Can sheet metal 8350

D-F-NL

300 ml Can sheet metal 8364

GB-ARAB-F

300 ml Can sheet metal 8342

D-PL-BG

300 ml Can sheet metal

7149

GB-HEB

300 ml Can sheet metal 7145

ALGERIEN-GB-ARAB-F

500 ml Can sheet metal 1013

D-F-NL

5 l Canister plastic

3710 D-GB

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de

Product information

Oil Additive

PI 39/12/02/2021



Available pack sizes

60 l Drum sheet metal 20606 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871 www.liqui-moly.com