

## Viscoplus for Oil

### Description

Modern, mono-functional high-performance additive for stabilizing the viscosity of motor oils. Visco Stabil offers outstanding protection against mechanical and therefore permanent shear losses to the oil under extreme running conditions and is effective against the thinning of motor oils due to frequent cold starts.

### Properties

- stabilizes loss of viscosity
- optimum lubrication under all operating conditions
- fully compatible with mineral and synthetic oils
- reduces engine noise
- optimum oil pressure under all operating conditions
- reduces oil consumption
- improves the movable seal between piston and cylinder
- reduces wear

### Technical data

Color / appearance	orange clear
Density at 20 °C	0,89 g/cm <sup>3</sup> DIN 51757
Viscosity at 20 °C	2400 mPas DIN 51377
Flash point	101 °C DIN ISO 2592
Pour point	-5 °C DIN ISO 3016
Odor	characteristic
Form	liquid

### Areas of application

For all passenger vehicles and commercial vehicles, gasoline and diesel engines in new and used vehicles.

### Comment

**Not suitable for use on motorbikes with wet clutches.**

### Application

Can contents (300 ml) are sufficient for 5 liters of motor oil. After adding to the motor oil, allow the engine to run warm. The product can be added at any time.

### Available pack sizes

300 ml Can sheet metal	2502 D-E-P
300 ml Can sheet metal	2807 DK-N-S-FIN

### Available pack sizes

300 ml Can sheet metal	2672 D-PL-BG
300 ml Can sheet metal	8362 GB-ARAB-F
300 ml Can sheet metal	8377 D-H-RO
300 ml Can sheet metal	8958 GB-GR-I
300 ml Can sheet metal	20916 JP
300 ml Can sheet metal	1017 D-F-NL

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

