Product information

Central Hydraulic System Oil

PI 51/03/03/2022 LIQU

Description

LIQUI MOLY central hydraulic system oils meet the highest technical requirements and are suitable for a wide range of automotive applications. The carefully selected formulations made from the best raw materials ensure excellent temperature properties and guarantee the full function of the systems even at the lowest temperatures of up to $-45~^{\circ}\text{C}$. All central hydraulic system oils are impressive thanks to excellent wear, aging and corrosion protection as well as optimum friction values and minimal foaming tendency.



- excellent viscosity/temperature properties
- optimum stability to aging
- highest thermal stability
- excellent low temperature behavior
- outstanding corrosion protection

Approvals

MAN M 3289

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

BMW 81 22 9 407 758 • Fiat 9.55550-AG3 • Ford WSS-M2C 204-A • MB 345.0 • Opel 1940 766 • VW G 002 000 • VW G 004 000 • ZF TE-ML 02K

Technical data

Flash point

Viscosity at 40 °C 19,6 mm²/s ASTM D 7042-04

Viscosity at 100 °C 6,4 mm²/s

ASTM D 7042-04

Viscosity index 322

DIN ISO 2909

Color / appearance green

Density at 15 °C 0,825 g/cm³
DIN 51757

150 °C

DIN ISO 2592

Pour point -72 °C

DIN ISO 3016

Foaming behavior at 24 °C 50/0 ml

ISO 6247

Foaming behavior at 93.5 °C 35/0 ml

ISO 6247



This synthetic hydraulic fluid with ash-free additives is ideally suited for steering systems, electro-hydraulic convertible tops, level controls, hydropneumatic suspensions, damping systems, cab tilting devices, etc.

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed. This oil can also be used for refilling in systems. Optimum effect only when the product is used unmixed.

Available pack sizes

1 l Can plastic 1158

D-NL-F-GR-ARAB

1 l Can plastic 1127

D-GB-I-E-P

1 l Can plastic 20468

PL-H-R0-TR

1 l Can plastic 2366

GB-DK-FIN-N-S

1 l Can plastic 9524

D-GB-F-ARAB

1 l Can plastic 21239

ALGERIEN-GB-ARAB-F

20 l Canister plastic 1147

D-GB-I-E-P

60 l Black plate barrel 1148

D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

Areas of application