Product information

Door Lock Care

PI 20/03/01/2022



Description

Specifically developed for lubricating and maintaining installed lock barrels and ignition locks. Use this care spray to keep movable parts permanently free and to deice frozen door locks.

Properties

- lasting corrosion protection
- does not attack plastics, rubber and paints
- outstanding lubricating action
- excellent de-icing properties
- friction and wear reducing

Technical data

Thickener Li-soap

Base oil fully synthetic

base oil

Operating temperature range -190 °C

Worked penetration 280 1/10 mm

DIN ISO 2137

NLGI number 2

DIN 51818

Color / appearance bright, slightly

transparent

Dropping point >185 °C

Base oil viscosity 40°C ca. 30 mm²/s
Base oil viscosity 100°C ca. 6 mm²/s
Flow pressure at -40 °C >1400 mbar

Behavior in the presence of 1-90

water

Four-ball tester material >2000 N

load/weld force

Areas of application

For lubricating, maintaining and de-icing door locks, door hinges and mechanical wing mirrors.

Application

Shake well before use. Insert the spray head into the lock barrel, push through and spray into the barrel.

Available pack sizes

50 ml Can aerosol 1528

D

Our information is based on thorough research and may be considered reliable, although not legally binding.



Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de