

Brake Anti-Squeal

Description

Brake Anti-Squeal Paste has been specially developed from synthetic and ceramic materials which eliminate brake squeals arising between the brake piston or contact surface and the brake lining.

Properties

- good corrosion protection
- easy to use
- eliminates squeaks
- resistant to road salt and splash water
- extremely low friction
- outstanding thermal stability
- outstandingly adherent
- ideally suited as a separating paste

Technical data

Form	pastelike, liquid
Color / appearance	blue
Base	synthetische u. keramische Wirkstoffe
Density	1,051 g/cm ³
Operating temperature range	-40 to +200 short term +250 °C
missing translation	als Schmierpaste / as lubricating agent -1240 °C als Trennpaste / as release agent
Flash point	>210 °C
Odor	slightly

Areas of application

Brake Anti-Squeal Paste has been specially developed for the assembly, repair and maintenance of brake systems. Used for basic lubrication and as a preventive measure against brake squeals. However, it is also universally suitable for numerous applications apart from brake systems.

Comment

Do not apply paste to the friction surface of the lining or the brake disk!

Shelf life in original sealed container:

10 g cushion plastic: 24 months

100 g tube plastic: 36 months

1 kg can sheet metal: 60 months



Application

With floating brake callipers, first clean all sliding surfaces, channels and contact surfaces using a brush or brake file. Next, clean the brake components with Rapid Cleaner (Part no. 3318). After the solvent has evaporated, coat cleaned parts with Brake Anti-Squeal Paste on all sliding surfaces, channels and contact surfaces.

Available pack sizes

10 g Cushion plastic	21121
	GB
100 g Tube plastic	3077
	D-GB-I
1 kg Can sheet metal	3084
	D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.