

## Radiator Antifreeze KFS 13

### Description

Combination of active agents which is formulated using an ingenious selection of inhibitors based on hybrid technology. Offers outstanding protection against frost, corrosion and overheating across its entire engine service life. Amine-, borate-, nitrite- and phosphate-free radiator antifreeze based on ethylene glycol.



### Properties

- contains no amines, borates, nitrites or phosphates
- outstanding corrosion protection
- provides outstanding protection against overheating
- protects the environment

### LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

Audi TL-774 J = G13 • Seat TL-774 J = G13 • Skoda TL-774 J = G13 • Volkswagen TL-774 J = G13

### Technical data

Density at 20 °C	1,132 g/cm <sup>3</sup>
Water content	3,4 % w/w max
pH value	8,6
Base	ethylene glycol with inhibitors
Color / appearance	bright red, clear
Flash point	122 °C
Boiling point	>170 °C
Odor	weak
Shelf life in original sealed container	36 months
Recommended storage temperature	-20 to +35 °C

### Areas of application

For engines made of cast iron, aluminum or a combination of the two as well as cooling systems with aluminum and/or copper alloys. Especially for all-alloy engines in which a special aluminum protection is required at higher temperatures. For passenger cars, commercial vehicles, buses, agricultural machines as well as stationary engines and devices that require a radiator antifreeze of this quality.

### Application

Clean the cooling system with LIQUI MOLY Radiator Cleaner (Part no. 3320). Empty the cooling system and rinse with plenty of water. Fill with radiator antifreeze KFS 13 and water according to the mixing table. We recommend distilled water for this. Depending on water hardness and quality (hardness not greater than 3.566 mmol/l), dilution with tap water is also possible. Disposal according to the local regulations. Change interval according to manufacturer's instructions. Store undiluted only. Miscible with coolants based on ethylene glycol.

### MIXING TABLE

Frost protection	Water	Protection up to
1 part	2 parts	-20 °C
1 part	1 part	-35 °C
2 parts	1 part	-69 °C

### Available pack sizes

1 l Canister plastic	21139
	D-GB
5 l Canister plastic	21140
	D-GB-I-E-P
20 l Canister plastic	21141
	D-GB-I-E-P
60 l Black plate barrel	21142
	D-GB

**Our information is based on thorough research and may be considered reliable, although not legally binding.**