

Motorbike Speed Shooter

Description

State-of-the-art, ash-free combination of agents with acceleration-enhancing, cleaning, dispersing and material-protecting properties. The product has been formulated using state-of-the-art additive and fuel technologies in accordance with the requirements of today's engines, fuels and running conditions. Ensures increased driving enjoyment due to optimized performance. The engine starts easier and also runs smoother.

Properties

- good corrosion protection
- residue-free combustion
- guarantees optimum combustion
- improves acceleration
- removes deposits from entire fuel system
- highly economical
- prevents carburetor icing
- higher performance gain

Technical data

Base	additive mixture in carrier fluid
Color / appearance	yellow, clear
Odor	characteristic
Form	liquid
Viscosity at 40 °C	<7 mm ² /s
Density at 20 °C	0,814 g/cm ³
Hazard class as per German VbF	A III
Flash point	>61 °C

Areas of application

For 2-stroke and 4-stroke gasoline engines (aspirated and injection).

Application

Add to the fuel tank. For the optimum effect, add every time you refuel. Fully compatible with all gasoline grades. 80 ml is sufficient for up to 10 liters of fuel.

Available pack sizes

80 ml Can sheet metal	7820
	GB
80 ml Can sheet metal	8265
	JP
80 ml Can sheet metal	7915
	VN



Available pack sizes

80 ml Can sheet metal	7823
	TR
80 ml Can sheet metal	20585
	ID

Our information is based on thorough research and may be considered reliable, although not legally binding.