

Description

Mixture of agents with cleaning, dispersing, and material-protection properties and has been formulated for today's engines, fuels and running conditions.

Properties

- highly economical
- guarantees low fuel consumption
- guarantees optimum combustion
- easier cold start in winter
- prevents seizing and the injector needles from gumming up
- prevents the build-up of deposits
- protects injection pumps, injector needles and cylinder/piston

Technical data

Base	additive mixture in carrier fluid
Density at 15 °C	0,8297 g/cm ³
Color / appearance	yellow, orange
Flash point	63 °C
Odor	n.a.
Form	liquid
Viscosity at 40 °C	<7 mm ² /s

Areas of application

Added to diesel fuel for all diesel engines in passenger and heavy goods vehicles, tractors, buses, construction machinery and stationary engines. Ideally suitable for preserving engines when decommissioned for long periods under extreme conditions.

Application

The content (1 litre) is sufficient for 400 l of diesel fuel. 1 measuring 25 ml cup (integrated in the screw cap) is sufficient for 10 litres of diesel fuel. The product mixes with the fuel automatically.

Available pack sizes

1 l Can sheet metal	2663
	D-PL-BG
1 l Can sheet metal	5160
	D

Our information is based on thorough research and may be considered reliable, although not legally binding.

