

Product information

megol Getriebeöl MTF GT1 75W



Description

High-performance gear oil especially for manual and automated manual transmissions. Particularly recommended for use in vehicles from Audi, BMW, Fiat, Ford, Seat, Škoda and VW.

Offers excellent shifting comfort under all operating conditions, fuel saving potential, excellent shear stability and optimum synchronous behavior. Thanks to the use of the highest quality raw materials, enables optimum wear and corrosion protection as well as outstanding resistance to oxidation.



Specifications / Approvals

API GL4

Meguin also recommends this product for vehicles that are subject to the following specifications

BMW 83 22 7 533 818 • BMW MTF LT-3 • Fiat 9.55550-MZ6 • Ford WSS-M2C 200-D2 • Toyota • VW G 052 178 • VW G 052 512 • VW G 052 726 • VW G 055 512 • VW G 060 726 • VW G 070 726

Characteristic data

SAE class (gear oils)	75W SAE J 306
Density at 15 °C	0,86 g/cm ³ DIN 51757
Viscosity at 40 °C	33,1 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	6 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	< 150000 mPas ASTM D 2983-09
Viscosity index	130 DIN ISO 2909
Pour point	-42 °C DIN ISO 3016
Flash point	224 °C DIN ISO 2592
Color number (ASTM)	L 2,5 DIN ISO 2049

Application

Shake well before use.

Available pack sizes

1 l Can plastic 33047
D-GB-F-HR-RUS-GR