

Product information

megol Getriebeöl MTF GT2 75W-80



Description

High-performance gear oil specifically for use in manual transmissions from BMW, Ford, Honda, Nissan, vehicles the PSA Group and other manufacturers. Also suitable for transaxle transmissions and transfer cases. Characterized by excellent wear protection, potential savings with regard to fuel consumption and emissions as well as optimum thermal and oxidative stability. Enable highly smooth, driver-friendly shifting operations with reduced shifting forces.



Specifications / Approvals

API GL4

Meguin also recommends this product for vehicles that are subject to the following specifications

BMW 83 22 0 309 031 • BMW 83 22 0 403 247 • BMW MTF LT-2 • BMW MTF LT-4 • Ford WSD-M2C 200-C • GM 1940764 • GM 1940768 • Nissan MT-XZ • Nissan MT-XZ TL (JR Type) • Peugeot Citroen (PSA) B71 2330 • Special Honda MTF-II • Toyota • Volvo 97308

Characteristic data

SAE class (gear oils)	75W-80 SAE J 306
Density at 15 °C	0,855 g/cm ³ DIN 51757
Viscosity at 40 °C	53 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	9,2 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	< 150000 mPas ASTM D 2983-09
Viscosity index	156 DIN ISO 2909
Pour point	-42 °C DIN ISO 3016
Flash point	216 °C DIN ISO 2592
Color number (ASTM)	L 2,0 DIN ISO 2049

Application

Shake well before use.

Available pack sizes

1 l Can plastic 33048
D-GB-F-HR-RUS-GR