

Product information

megol Getriebeöl MTF GT3 70W-75W



Description

Low-viscosity, fully synthetic high-performance gear oil especially for manual and automated manual transmissions. Recommended particularly for use in vehicles from Audi, Seat, Škoda and Volkswagen. Offers excellent oxidation and wear protection as well as high fuel saving potential. Ensures excellent driving comfort under all operating conditions. Shear stability and synchronous behavior at the highest level guarantee optimum workflows.



Specifications / Approvals

API GL4

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Hyundai • Kia • VW G 052 171 • VW G 052 527

Characteristic data

SAE class (gear oils)	70W-75W SAE J306
Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	30,8 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	5,9 mm ² /s ASTM D 7042-04
Viscosity at -55 °C (Brookfield)	< 150000 mPas ASTM D 2983-09
Viscosity index	139 DIN ISO 2909
Pour point	< -60 °C DIN ISO 3016
Flash point	220 °C DIN ISO 2592
Color number (ASTM)	L 2,5 DIN ISO 2049

Application

Shake well before use.

Available pack sizes

1 l Can plastic 33049
D-GB-F-HR-RUS-GR