

Product information

megol Hypoid-Getriebeöl GL 4+ SAE 75W-90



Description

Fully synthetic multigrade gear oil with corrosion protection and high-pressure properties for low and high temperatures. Friction reduction contributes to fuel savings. A multi-purpose gear oil with a broad application range in vehicle transmissions, mainly in manual transmissions. Shifting problems and noise development in manual transmissions are eliminated at low temperatures. Due to the fully synthetic base oils in combination with modern additive technology, this lubricant guarantees outstanding wear protection under all operating conditions in summer and winter operation; also suitable for arctic climates.



Available pack sizes

1 l Bulk goods 9205
D

Specifications / Approvals

API GL4+

Meguin also recommends this product for vehicles that are subject to the following specifications

Ford ESD-M2C 175-A • VW 501 50 (G50) • ZF TE-ML 08A • MIL-L 2105

Characteristic data

SAE class (gear oils)	75W-90 SAE J306
Density at 15 °C	0,855 g/cm ³ DIN 51757
Viscosity at 40 °C	81,5 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,3 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	183 DIN ISO 2909
Pour point	-60 °C DIN ISO 3016
Flash point	200 °C DIN ISO 2592
Color number (ASTM)	L 1,5 DIN ISO 2049

Available pack sizes

1 l Can plastic	3535 D-GB-F-HR-RUS-GR
20 l Canister plastic	8616 D-GB
60 l Black plate barrel	6668 D-GB
200 l Black plate barrel	8618 D-GB