

Product information

megol Hypoid-Getriebeöl GL 5 SAE 75W-140 LS



Description

Fully synthetic gearbox oil with LS-additive (LS=limited slip) for use in motor vehicles, preferably BMW's with locked axle systems and in axles, manual gearboxes and auxiliary drives with extended oil-change intervals in commercial vehicles. megol Hypoid-Getriebeöl GL 5 SAE 75W- 140 LS is suited for a wide temperature range because of the adjusted SAE-class.



Approvals

API GL5 • VME

Meguin also recommends this product for vehicles that are subject to the following specifications

BMW rear-axle gear oil • Ford WSL-M2C 192-A • Scania STO 1:0 • ZF TE-ML 05D • ZF TE-ML 12D • ZF TE-ML 16G

Characteristic data

SAE class (gear oils)	75W-140 SAE J306
Density at 15 °C	0,875 g/cm ³ DIN 51757
Viscosity at 40 °C	179 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	25 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	172 DIN ISO 2909
Pour point	-51 °C DIN ISO 3016
Flash point	208 °C DIN ISO 2592
Color number (ASTM)	L 1,5 DIN ISO 2049

Available pack sizes

1 l Canister plastic 3536
D-GB-F-HR-RUS-GR