

Product information

megol Motorenoel Efficiency SAE 5W-30



Description

High-performance motor oil based on Low-SAPS technology, which was specially developed for exhaust aftertreatment systems on the latest generation of diesel engines. Also suitable for gasoline engines. Meets the high performance requirements of modern engines and ensures maximum service life of the diesel particulate filter as well as low wear, clean engine operation and long oil change intervals.

Note the manufacturer's instructions!

Specifications / Approvals

ACEA C2 • ACEA C3 • API SP • BMW Longlife-04 • MB-Approval 229.31 • MB-Approval 229.51 • MB-Approval 229.52 • Opel OV 040 1547 - G30 / OV 040 1547 - D30

Meguin also recommends this product for vehicles that are subject to the following specifications

Fiat 9.55535-S3 • Ford WSS-M2C 917-A • GM dexos2 • Opel GM-LL-A-025 • Opel GM-LL-B-025 • VW 505 00 • VW 505 01

Characteristic data

SAE class (engine oils)	5W-30 SAE J300
Density at 15 °C	0,850 g/cm ³ DIN 51757
Viscosity at 40 °C	71,0 mm ² /s ASTM D7042
Viscosity at 100 °C	12,2 mm ² /s ASTM D7042
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	<= 6600 mPas ASTM D5293
Viscosity index	170 DIN ISO 2909
HTHS at 150°C	≥ 3,5 mPas ASTM D5481
Pour point	-39 °C DIN ISO 3016
Evaporation loss (Noack)	9,0 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	7,5 mg KOH/g DIN ISO 3771
Sulfate ash	≤ 0,8 g/100g DIN 51575

Characteristic data

Color number (ASTM)	2,5
	DIN ISO 2049

Available pack sizes

1 l Canister plastic	3196 D-GB-F-ARAB-RUS-RO-I-E-P
4 l Canister plastic	33062 D-GB-F-ARAB-RUS-RO-I-E-P
5 l Canister plastic	3194 D-GB-F-ARAB-RUS-RO-I-E-P
20 l Canister plastic	9480 D-GB
60 l Black plate barrel	9481 D-GB
200 l Black plate barrel	9482 D-GB
1.000 l Deposit container	9483 D-GB