

# Product information

## megol Motorenoel Ultra Performance Longlife SAE 5W-40



### Description

Modern low-friction motor oil based on HC synthetic oils. Its perfectly tailored combination of additives reliably prevents the formation of deposits, reduces frictional losses in the engine and optimally protects against wear. This results in fuel savings and extended service life of the engine. Offering a wide range of applications, it is ideally suited for vehicles with gasoline and diesel engines (without diesel particulate filter) with and without turbocharger.

**Range of applications: Passenger cars.**

**SAPS level: High-SAPS.**

**Note the manufacturer's instructions!**

### Specifications / Approvals

ACEA A3 • ACEA B4 • API SN PLUS • API CF • BMW Longlife-98 • MB-Approval 229.3 • VW 502 00 • VW 505 00

**Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:**

Fiat 9.55535-H2 • Fiat 9.55535-M2

### Characteristic data

SAE class (engine oils)	5W-40 SAE J300
Density at 15 °C	0,855 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	83,0 mm <sup>2</sup> /s ASTM D7042
Viscosity at 100 °C	13,9 mm <sup>2</sup> /s ASTM D7042
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	≤ 6600 mPas ASTM D5293
Viscosity index	170 DIN ISO 2909
HTHS at 150°C	> 3,5 mPas ASTM D5481
Pour point	-36 °C DIN ISO 3016
Evaporation loss (Noack)	11,0 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592

### Characteristic data

Total base number	11,0 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color number (ASTM)	L 3,0 DIN ISO 2049

### Available pack sizes

1 l Canister plastic	4361 AR-DE-EN-ES-FR-IT-PT-RO-RU
4 l Canister plastic	6486 AR-DE-EN-ES-FR-IT-PT-RO-RU
5 l Canister plastic	6328 AR-DE-EN-ES-FR-IT-PT-RO-RU
20 l Canister plastic	4359 DE-EN
60 l Black plate barrel	4358 DE-EN
200 l Black plate barrel	6398 DE-EN
1.000 l Deposit container	9777 DE-EN
1 l Bulk goods	6860 DE