

Product information

megol Motorenoel Premium Performance SAE 0W-20



Description

Premium motor oil with outstanding performance. Manufactured based on the best raw materials and cutting edge technologies. Offers outstanding lubricating film, aging and shear stability, optimum wear protection and maximum engine cleanliness. Ensures perfect engine running under all temperature and operating conditions and enables the reduction of the fuel consumption.

Range of applications: Car.

SAPS level: Low-SAPS

Note manufacturer's instructions!

Specifications / Approvals

ACEA C5, C6 • API SP • ILSAC GF-6A • BMW Longlife-17 FE+ • MB-Approval 229.71 • MB-Approval 229.72 • Opel OV 040 1547 - A20

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Chrysler MS-12145 • Fiat 9.55535-GSX • Ford WSS-M2C 947-B1 • Ford WSS-M2C 954-A1 • Ford WSS-M2C 962-A1 • Jaguar / Land Rover STJLR.03.5006

Characteristic data

SAE class (engine oils)	0W-20 SAE J300
Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	43 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	8,5 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -35 °C (CCS)	≤ 6200 mPas ASTM D 5293
Viscosity index	180 DIN ISO 2909
HTHS at 150°C	≥ 2,6 mPas ASTM D 5481
Pour point	-48 °C DIN ISO 3016
Evaporation loss (Noack)	11 % CEC-L-10-A-93

Characteristic data

Flash point	230 °C DIN ISO 2592
Total base number	8,3 mg KOH/g DIN ISO 3771
Sulfate ash	≤ 0,8 % DIN 51575
Color number (ASTM)	L 3,0 DIN ISO 2049

Application

The specifications and instructions from the unit or vehicle manufacturer must be followed. Optimum effect only when the product is used unmixed.

Available pack sizes

1 l Canister plastic	33068 D-GB-F-ARAB-RUS-RO-I-E-P
4 l Canister plastic	33073 D-GB-F-ARAB-RUS-RO-I-E-P
5 l Canister plastic	33069 D-GB-F-ARAB-RUS-RO-I-E-P
20 l Canister plastic	33070 D-GB
60 l Black plate barrel	33071 D-GB
200 l Black plate barrel	33072 D-GB