

Product information

megol Motorenoel Quality SAE 5W-30



Description

Modern multigrade low-friction motor oil for year-round use. Guaranteed low viscosity and high shear stability thanks to synthetic HC base oils and modern additive technology. This product reliably prevents the formation of deposits, reduces frictional losses in the engine and optimally protects against wear. This results in fuel savings and extended service life of the engine. Recommended for vehicles with gasoline and diesel engines without diesel particulate filter (DPF), including those with a turbocharger and catalytic converter.

Range of applications: Car.

SAPS level: High-SAPS.

Note the manufacturer's instructions!

Specifications / Approvals

ACEA A3 • ACEA B4 • API CF • API SL • MB-Approval 229.5 • VW 502 00 • VW 505 00

Meguin also recommends this product for vehicles that are subject to the following specifications

BMW Longlife-01 • Opel GM-LL-A-025 • Opel GM-LL-B-025 • Renault RN 0700

Characteristic data

Density at 15 °C	0,855 g/cm ³ DIN 51757
Viscosity at 40 °C	72 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	12 mm ² /s ASTM D 7042-04
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	≤ 6600 mPas ASTM D5293
Viscosity index	165 DIN ISO 2909
High temperature/high shear viscosity	≥ 3,5 ASTM D5481
Pour point	-42 °C DIN ISO 3016
Evaporation loss (Noack)	9,5 % CEC L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	11,2 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575

Characteristic data

Color number (ASTM) L 3,5
DIN ISO 2049

Available pack sizes

1 l Canister plastic	6566 D-GB-F-ARAB-RUS-RO-I-E-P
4 l Canister plastic	9027 D-GB-F-ARAB-RUS-RO-I-E-P
5 l Canister plastic	6567 D-GB-F-ARAB-RUS-RO-I-E-P
20 l Canister plastic	6568 D-GB
60 l Black plate barrel	6582 D-GB
200 l Black plate barrel	6687 D-GB
1.000 l Container	8497 D-GB
1 l Bulk goods	6857 D