

Product information

megol Motorenoel Super Leichtlauf DRIVER SAE 0W-40



Description

Fully synthetic low-friction motor oil for year-round use. Thanks to synthetic base oils and adapted additive technology, reliably prevents the formation of deposits, reduces frictional losses in the engine and optimally protects against wear. This results in fuel savings and extended service life of the engine. Recommended for gasoline and diesel engines, including those with turbochargers and catalytic converters.

Range of applications: Passenger cars.

SAPS level: High-SAPS.

Note the manufacturer's instructions!

Specifications / Approvals

ACEA A3 • ACEA B4 • API SN • API CF

Meguin also recommends this product for vehicles that are subject to the following specifications

BMW Longlife-98 • MB 229.3 • Ford WSS-M2C 937-A • Opel GM-LL-B-025 • Porsche A40 • VW 502 00 • VW 505 00

Characteristic data

SAE class (engine oils)	0W-40 SAE J300
Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	80,0 mm ² /s ASTM D7042
Viscosity at 100 °C	13,8 mm ² /s ASTM D7042
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -35 °C (CCS)	≤ 6200 mPas ASTM D5293
Viscosity index	180 DIN ISO 2909
HTHS at 150°C	≥ 3,7 mPas ASTM D5481
Pour point	-48 °C DIN ISO 3016
Evaporation loss (Noack)	10,0 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592

Characteristic data

Total base number	10,5 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color number (ASTM)	L3,0 DIN ISO 2049

Available pack sizes

1 l Canister plastic	4894 D-GB-F-ARAB-RUS-RO-I-E-P
4 l Canister plastic	9065 D-GB-F-ARAB-RUS-RO-I-E-P
5 l Canister plastic	4895 D-GB-F-ARAB-RUS-RO-I-E-P
20 l Canister plastic	4896 D-GB