

Product information

megol Motorenoel Super Performance SAE 10W-40
(teilsynthetisch)



Description

Low-friction motor oil for year-round use. Thanks to its synthetic and mineral base oils and modern additive technology, reduces the friction losses of the engine, protects against wear and thus prolongs the life of the engine. To ensure full performance, avoid mixing with other motor oils.

Range of applications: Passenger cars.

SAPS level: High-SAPS.

Note the manufacturer's instructions!

Specifications / Approvals

ACEA A3 • ACEA B3 • API CF • API SL

Meguin also recommends this product for vehicles that are subject to the following specifications

MB 229.1

Characteristic data

SAE class (engine oils)	10W-40 SAE J300
Density at 15 °C	0,865 g/cm ³ DIN 51757
Viscosity at 40 °C	95,0 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,5 mm ² /s ASTM D 7042-04
Viscosity at -30 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -25 °C (CCS)	<= 7000 mPas ASTM D5293
Viscosity index	160 DIN ISO 2909
HTHS at 150°C	>= 3,5 mPas ASTM D5481
Pour point	-36 °C DIN ISO 3016
Evaporation loss (Noack)	10,0 % ASTM D 5800-08 Method B
Flash point	230 °C DIN ISO 2592
Total base number	10,3 mg KOH/g DIN ISO 3771
Sulfate ash	0,9 - 1,5 g/100g

Characteristic data

Color number (ASTM) L 4,0
DIN ISO 2049

Available pack sizes

1 l Canister plastic	4366 D-GB-F-ARAB-RUS-RO-I-E-P
4 l Canister plastic	3517 D-GB-F-ARAB-RUS-RO-I-E-P
5 l Canister plastic	4365 D-GB-F-ARAB-RUS-RO-I-E-P
60 l Black plate barrel	6460 D-GB
200 l Black plate barrel	6491 D-GB
1.000 l Deposit container	9779 D-GB