

# Product information

## megol Zentralhydraulikoel



### Description

Special hydraulic oil based on synthetic and mineral oil with ash-free additives to improve viscosity, friction value, wear protection, oxidation protection, foam and corrosion protection. It has optimum performance as a central hydraulic system oil in power steering systems, level control, hydraulic brake servo unit and hydropneumatic suspension. The special formulation of megol Central Hydraulic System Oil ensures excellent low-temperature properties and is therefore particularly suitable for use in cold countries.



Note the manufacturer's instructions.

### Meguin also recommends this product for vehicles that are subject to the following specifications

BMW 81 22 9 407 758 • Ford WSS-M2C 204-A • MAN M 3289 • MB 345.0 • Opel 1940 766 • VW G 004 000 • VW G 002 000 • ZF TE-ML 02K

### Characteristic data

Viscosity at 40 °C	19,5 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	6,1 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity index	300 DIN ISO 2909
Color / appearance	green
Density at 15 °C	0,825 g/cm <sup>3</sup> DIN 51757
Flash point	150 °C DIN ISO 2592
Pour point	-51 °C DIN ISO 3016
Foaming behavior at 24 °C	50/0 ml ISO 6247
Foaming behavior at 93.5 °C	35/0 ml ISO 6247

### Application

Shake well before use.

### Available pack sizes

1 l Canister plastic	6304 D
20 l Canister plastic	8641 D-GB