

Product information

megol Special Engine Oil SAE 0W-16



Description

Modern high-performance motor oil. Thanks to selected HC base oils in combination with perfectly tailored additives, particularly suitable for gasoline engines for the Asian and American markets. Keeps the engine clean, offers high shear stability and minimizes wear. Ensures quick oil penetration as well as smooth engine running under all operating conditions and is therefore very well suited to the high demands of modern engines. The low viscosity class enables a reduction of fuel consumption.



Note the manufacturer's instructions!

Specifications / Approvals

API SQ • ILSAC GF-7B

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Honda • Lexus • Suzuki • Toyota

Characteristic data

SAE class (engine oils)	0W-16 SAE J 300
Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	38,0 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	7,2 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -35 °C (CCS)	≤ 6200 mPas ASTM D 5293
Viscosity index	155 DIN ISO 2909
HTHS at 150°C	≥ 2,3 mPas ASTM D 5481
Pour point	-45 °C DIN ISO 3016
Evaporation loss (Noack)	12,5 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	8,3 mg KOH/g DIN ISO 3771
Sulfate ash	0,9 g/100g DIN 51575

Characteristic data

Color number (ASTM) L 2,5
DIN ISO 2049

Available pack sizes

1 l Canister plastic	33055 AR-DE-EN-ES-FR-IT-PT-RO-RU
4 l Canister plastic	33056 AR-DE-EN-ES-FR-IT-PT-RO-RU
5 l Canister plastic	33057 AR-DE-EN-ES-FR-IT-PT-RO-RU