

Product information

megol Special Engine Oil SAE 5W-30



Description

Modern high-performance motor oil. Thanks to the selected HC base oils in combination with the suitable additives, it has optimum properties specially formulated for gasoline engines on the Asian and American markets. Keeps the engine clean, offers high shear stability and minimizes wear. Ensures rapid oil penetration and smooth engine running under all operating conditions. Is thus very well suited for the high demands of modern engines. Note the manufacturer's instructions!

Specifications / Approvals

API SQ • ILSAC GF-7A

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Chrysler MS-6395 • Fiat 9.55535-CR1 • Ford WSS-M2C 946-A • Ford WSS-M2C 946-B1 • Ford WSS-M2C 961-A1 • GM 6094 M • GM dexos1 Gen 3 • Honda • Mazda • Mitsubishi Dia Queen • Nissan • Toyota

Characteristic data

SAE class (engine oils)	5W-30 SAE J300
Density at 15 °C	0,850 g/cm ³ DIN 51757
Viscosity at 40 °C	60,0 mm ² /s ASTM D7042
Viscosity at 100 °C	10,8 mm ² /s ASTM D7042
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	≤ 6600 mPas ASTM D5293
Viscosity index	170 DIN ISO 2909
HTHS at 150°C	> 2,9 mPas ASTM D5481
Pour point	-39 °C DIN ISO 3016
Evaporation loss (Noack)	10,5 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	7,5 mg KOH/g DIN ISO 3771
Sulfate ash	0,9 g/100g DIN 51575

Characteristic data

Color number (ASTM)	L 2,5 DIN ISO 2049
Oil base	Advanced Full Synthetic

Available pack sizes

1 l Canister plastic	33100 AR-DE-EN-ES-FR-IT-PT-RO-RU
4 l Canister plastic	33101 AR-DE-EN-ES-FR-IT-PT-RO-RU
5 l Canister plastic	33102 AR-DE-EN-ES-FR-IT-PT-RO-RU
20 l Canister plastic	33103 DE-EN
60 l Black plate barrel	33104 DE-EN
200 l Black plate barrel	33105 DE-EN